

WP200A

SPECIFICATIONS

| Model | WP200A |
|---------------------------------|--------------------------------------|
| Welding range (mm) | 63-200 |
| Standard reducers (mm) | 63-75-90-110-125- 140-160-180-200 |
| Power supply | 220V/50Hz, 1PH |
| Total power | 3.65 KW |
| Heating plate | 1.8 KW |
| Planing tool | 1.1KW |
| Hydraulic station | 0.75KW |
| Pressure adjusting range | 0-8 MPa |
| MaxTemperature of heating plate | 270°C |
| Temperature Deviation | ±5°C |



FEATURING

For use on building sites, drain pipe laying, and in the workshop.

Suitable for PE, PP, PVDF

Integrated die casting aluminum frame, high-strength steel base with cylinder, provides stable heavy-duty performance.

Planing tool with full-gear transmission structure. Durable and long life HSS blade.

Heating plate with high quality PTFE coating, enables swift temperature control.

Hydraulic station of integrated enclosure shielding splash & dirt

STANDARD PARTS

| | |
|-------------------|------------------|
| Machine frame | 1 set |
| Heating plate | 1 set |
| Planing tool | 1 set |
| Hydraulic station | 1 set |
| Reducers | 1 set (63-200mm) |

Optional parts: Flange holder, Single angle insert, Data logging device