



# WP250A

## SPECIFICATIONS

| Model                           | WP250A                                 |
|---------------------------------|--|
| Welding range (mm)              | 63-250                                 |
| Standard reducers (mm)          | 90-110-125-140-160-180-200<br>-225-250 |
| Optional reducers (mm)          | 63-75                                  |
| Power supply                    | 220V/50Hz, 1PH                         |
| Total power                     | 5.05 KW                                |
| Heating plate                   | 2.3 KW                                 |
| Planing tool                    | 2.0 KW                                 |
| Hydraulic station               | 0.75 KW                                |
| Pressure adjusting range        | 0-8 MPa                                |
| MaxTemperature of heating plate | 270°C                                  |
| Temperature Deviation           | ±5°C                                   |



## FEATURING

- For use on building sites, drain pipe laying, and in the workshop.
- Suitable for PE, PP, PVDF
- Integrated die casting aluminum frame, high-strength steel base with cylinder, provides stable heavy-duty performance.
- Planing tool with full-gear transmission structure. Durable and long life HSS blade.
- Heating plate with high quality PTFE coating, enables swift temperature control.
- Hydraulic station of integrated enclosure shielding splash & dirt

## STANDARD PARTS

|                   |                  |
|-------------------|------------------|
| Machine frame     | 1 set            |
| Heating plate     | 1 set            |
| Planing tool      | 1 set            |
| Hydraulic station | 1 set            |
| Reducers          | 1 set (90-250mm) |

Optional parts: Flange holder, Single angle insert, Data logging device